

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification:

G06K 5/00, 7/01, 19/00, G06F 17/00,  
17/60

A1

(11) International Publication Number:

WO 98/10363

(43) International Publication Date:

12 March 1998 (12.03.98)

(21) International Application Number: PCT/US97/15584

(22) International Filing Date: 5 September 1997 (05.09.97)

(30) Priority Data:

08/711,449


6 September 1996 (06.09.96) US

(71) Applicant: LCI COMPUTER GROUP [NL/US]; 242 Neck  
Road, Ward Hill, MA 01835 (US).(72) Inventor: DE SCHRIJVER, Stefaan, A.; 952 Beacon Street,  
Newton, MA 02159 (US).(74) Agents: KELLY, Edward, J. et al.; Foley, Hoag & Eliot LLP,  
One Post Office Square, Boston, MA 02109 (US).(81) Designated States: JP, KR, European patent (AT, BE, CH, DE,  
DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

## Published

*With international search report.**Before the expiration of the time limit for amending the  
claims and to be republished in the event of the receipt of  
amendments.*

(54) Title: SYSTEMS FOR READING THE BALANCE OF AN ELECTRONIC MONEY CARD AND PROCESSES FOR MANUFACTURING THE SAME



## (57) Abstract

The invention relates to an electronic assembly that forms a balance reader system of reading balance of an electronic money card and that is integrated into the sidewall of a wallet, as well as the method for making the same. The figure shows an electronic circuit assembly (36) housed within the card sleeve (28). The electronic assembly (36) includes a display element (38), an electronic circuit (40), a first battery (44), a second battery (46), a switch element (50), and a telecommunications interface (52).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NI	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

**SYSTEMS FOR READING THE BALANCE  
OF AN ELECTRONIC MONEY CARD AND  
PROCESSES FOR MANUFACTURING THE SAME**

**Field of the Invention**

The invention relates to systems for reading the balance of an electronic money card and processes for manufacturing such systems and, in particular, to systems that include a balance reader integrated into a wallet and processes for  
5 manufacturing the same.

**Background of the Invention**

Electronic money cards are now widely used for transacting business. Generally, these electronic money cards are credit card size electronic devices  
10 that have a data port that can be connected into an electronic money transaction machine that increases or decreases the balance stored on the money card, depending upon the transaction performed. For example, the electronic money card can be inserted into an electronic bank machine that can increase the balance stored on that card to represent thereby the withdrawal of  
15 funds from the bank. Conversely, the electronic money card can be inserted into an electronic cash register machine that can decrease the balance on the card responsive to a purchase of goods.

Electronic money cards work well for carrying and storing data signals representative of electronic money. However, unlike conventional hard  
20 currency, electronic money signals are not readily discernible by a user wishing to determine the amount of money available to that user. Accordingly,

electronic money cards require a balance reader that allows the user to determine the balance stored on that card. Typically, these balance readers are electronic circuit card assemblies sized to receive a money card, with a port for slidably receiving the electronic money card and with a display that can display  
5 to a user the balance stored in that card. Although these balance readers generally work well, they tend to be bulky, and complicated plastic cases that are cumbersome to carry.

Accordingly, it is an object of the invention to provide balance readers that are more facile to use and more convenient to carry.

10 Other objects of the invention shall be made obvious by the review of the attached figures and upon study of the associated detailed description.

#### Summary of the Invention

The invention provides a balance reader for reading an electronic  
15 money card. The balance reader according to the invention is integrated into a sidewall of a wallet to provide a balance reader that is easy to carry and facile to use.

In one aspect, the invention is understood as an apparatus for reading the balance of an electronic money card. Such apparatus includes a wallet  
20 having a first sidewall, and a card sleeve coupled to the sidewall and having a first partition that houses a balance reader which includes a contact for electrically communicating with a terminal point of the electronic money card, a second partition disposed adjacent to the first partition and dimensioned for slidably receiving an electronic memory card, and a contact port coupling the  
25 first partition to the second partition and disposed between the partitions to allow the contact to electrically couple with the terminal point.

In one embodiment, the card sleeve is formed of a non-conductive material, such as plastic, vinyl, rubber, or any other non-conductive material.

The balance readers of the invention can include a printed circuit board assembly, wherein the balance reader comprises an electrical circuit card  
5 assembly disposed upon a printed circuit board. The printed circuit board can be a flexible circuit board of the type that can be bent and folded. Alternatively, the balance reader can include an electronic assembly that is formed on the first sidewall of the wallet. In this embodiment, the sidewall of the wallet can be leather, canvas, plastic, or any other material suitable for  
10 forming wallets.

In a further embodiment, systems according to the invention include a telecommunications element for exchanging data signals across a telephone communication line. The telecommunication system can include an acoustic coupler, or can further include an electronic connection element for connecting  
15 to a telephone communication system and for transmitting electrical data signals across a telephone network. The electronic connection element can be, in one embodiment, a conventional telephone plug for connecting with a telephone jack.

In a further aspect, the invention can be understood as processes for  
20 manufacturing a balance reader for an electronic money card. Processes according to the invention comprise the steps of providing a wallet having a first sidewall, and applying to that sidewall a conductive material to form a circuit pattern for the balance reader. Optionally, processes of the invention can include the further step of mounting circuit elements to the sidewall to  
25 form a circuit assembly thereon. In this aspect, the step of applying a conductive material to the sidewall can include the step of providing a mask

over the sidewall, as well as applying a conductive paste to the sidewall, or further applying a conductive ink to the sidewall.

#### Brief Description of the Illustrated Embodiments

5        FIG. 1 depicts a wallet according to the present invention that has a balance reader integrated into the sidewall of the wallet;

FIG. 2 illustrates a sleeve suitable for use with the wallet depicted in FIG. 1;

FIG. 3 depicts a balance reader incorporated into one partition of the sleeve depicted in FIG. 2; and

10        FIG. 4 depicts an interior wall of the sleeve depicted in FIG. 2 having a contact port that extends through the wall.

#### Description of the Illustrated Embodiments

15        FIG. 1 depicts one embodiment of the invention that can be a wallet 10 having a first sidewall 12, a second sidewall 14, a balance reader 16 with a display 18, and a receiving port 20.

As depicted by FIG. 1, the balance reader 16 is integrated into the sidewall 12 of the wallet 10. The bank card 22 depicted in FIG. 1 can be slid  
20        into the receiving port 20 to be read by the balance reader 16. The balance on the card 22 will be depicted in display 18 to alert the user as to the balance remaining on the card 22.

FIG. 2 depicts a card sleeve 28 that includes a first sidewall 30, a second sidewall 32, and an interior partition wall 34. As depicted in FIG. 2, the first  
25        sidewall 30 and the partition wall 34 form a first partition and, similarly, the second sidewall 32 and the partition wall 34 form a second partition within the

card sleeve 28. The depicted card sleeve 28 can be a conventional plastic credit card sleeve suitable for holding a first and second credit card within the respective first and second partition formed by the sidewalls 30 and 32 and the partition wall 34.

5       The card sleeve 28 can be integrated into the wallet 10 by attaching the exterior face of one of the sidewalls 30 or 32 to the sidewall 12 of the wallet 10 depicted in FIG. 1. For example, the card sleeve 28 depicted in FIG. 2 can be mechanically attached to the sidewall 12 and the depicted wallet 10 in FIG. 1 by gluing the exterior of the sidewall 32 against the sidewall 12. Alternatively,  
10       the card sleeve 28 can be stitched against a wallet sidewall 12 to attach the sleeve 28 into the wallet 10. As will be seen from the following, the card sleeve 28 forms a housing that can house a balance reader for reading the balance of an electronic money card and that can provide a partition which can slidably  
15       receive an electronic money card to be read by the balance reader incorporated into the card sleeve 28. In this way, the invention provides a thin, compact, and easy to use balance reader that is incorporated into a wallet.

FIG. 3 depicts an electronic assembly that forms a balance reader suitable for reading the balance of an electronic money card. As illustrated, FIG. 3 provides a cut-away view of electronic circuit assembly 36 housed  
20       within the card sleeve 28, in that the exterior wall, either 30 or 32 of card sleeve 28, is not depicted to show in detail the electronic circuit assembly 36 of the balance reader housed within the card sleeve 28. The depicted electronic circuit assembly 36 includes a display element 38, an electronic circuit 40, a first battery 44, a second battery 46, a switch element 50, and a telecommunications  
25       interface 52.

The circuit assembly 36 can be fitted within one of the partitions formed within the card sleeve 28. In one example, the circuit assembly 36 is fitted within the first partition of card sleeve 28 formed between the sidewall 30 and the inner partition wall 34. In this embodiment, the circuit assembly 36 is fixably attached to the partition wall 34 to prevent the circuit assembly 36 from moving. The balance reader depicted in FIG. 3 can be a conventional balance reader of the type of manufactured and sold by Oki Electronics Corporation of Tokyo, Japan. In this embodiment, the electronic circuit assembly reader operates responsive to activation of the dome switch 50 depicted in FIG. 3 that makes contact with the battery 44 and 46 and causes the circuit 40 of the balance reader 36 to power up. By application of pressure against the circuit card 36, contact points on the opposite side of the board 36 (not shown) can be pushed against the leads of a purse card placed adjacent to the circuit card 36. Upon forming an electrical connection between the contact points of the circuit assembly 36 and the leads of the money card 22, the electronic 40 perform a read operation that reads the balance of the purse card 22. The balance is then displayed by the display element 38.

It will be apparent to one of ordinary skill in the art of electrical engineering that any circuit assembly 36 suitable for being fixed within the card sleeve 28 can be practiced with the present invention, and subtractions and modifications to the circuit assembly 36 described herein did not depart from the scope of the invention. In particular, alternative embodiments of the circuit assembly 36 can be provided that employ an amphenol contacting switch element which incorporates the contacting switch in a single device. The amphenol device can be used instead of the dome switch 50 depicted in FIG. 3 for activating the circuit 40 to read the balance of the purse card 22.



Further embodiments of the circuit assembly 36 can be practiced with the invention without departing from the scope thereof.

In the embodiment depicted in FIG. 3, the circuit card 36 includes a telecommunication element 52. The telecommunication element 52 can allow  
5 the circuit assembly 36 to couple to a telecommunication system to transmit data across the public switching telephone network (PSTN). In one embodiment, the assembly 36 includes a modem chip and a miniature loud speaker and microphone to form an acoustic coupler. In this embodiment, the microphone element can be incorporated in one of the sidewalls of the wallet  
10 10 depicted in FIG. 1 and the loudspeaker element can be depicted in the opposite sidewall of the wallet 10. The loudspeaker and the microphone elements can be separated by a distance of approximately 165 millimeters or other distance suitable for providing an acoustic coupler that can be placed against the handset of a telephone couple the loudspeaker to the mouthpiece of  
15 the telephone handset and to couple the microphone to the ear piece of the handset to transmit data across the PSTN.

In an alternative embodiment, a telecommunication element 52 provides a telephone jack to allow a telephone cord to connect to the circuit card 36. In this embodiment, a telephone jack can be directly coupled to the  
20 electronics of the card 36 and the modem chip can negotiate the transfer of data between the card 36 and a remote site. Other embodiments for allowing the balance reader to transmit data across the public switching telephone network can practice with the present invention without departing from the scope thereof.

FIG. 4 depicts a partition wall 34 that includes a contact port 56 that couples the first partition of the card sleeve 28 to the second partition of the card sleeve 28. Further, the contact port 56 is disposed between the two partitions to allow the contact of the balance reader to couple with the terminal point of the electronic money card. As depicted in FIG. 4, this embodiment provides the contact port 56 at one end of the partition wall 34 to provide a port that extends between the wall 34 and which allows the circuit assembly 36 to electrically couple to a purse card 22 by allowing contact points on the circuit assembly 36 to electronically couple, i.e. contact, the lead terminals of the purse card 22. In this way, when the purse card 22 slid into the second partition of the card sleeve 28 and pressure is applied to the exterior of the card sleeve 28 to contact the contact terminals against the lead terminals, the circuit assembly 36 reads the balance of the card 22 and displays it in the display element 18 depicted in FIG. 1.

It will be apparent to one of ordinary skill in the art of electrical engineering, that any electrical interconnection suitable for electrically coupling the circuit assembly 36 with the purse card 22 can be practiced with the present invention without departing from the scope thereof, and that such an electrical connection can be formed upon sliding the purse card 22 within the second partition of the credit card sleeve 28 with sufficient pressure to form a mechanical contact between the terminal points and the leads.

In an alternative embodiment of the invention, the circuit assembly 36 depicted in FIG. 3 can be formed directly onto the material of the wallet sidewall 12 depicted in FIG. 1. In this embodiment, a conductive material can be placed upon the sidewall 12 to form a circuit pattern for the balance reader. Upon formation of the circuit pattern, circuit elements can be mounted to the

sidewall 12 to form a circuit assembly thereon. The circuit assembly formed on the sidewall 12 of the wallet 10 can function as the circuit assembly 36 depicted in FIG. 3. In this practice of the invention, the conductive material can be formed on the sidewall 12 using a masking operation where a mask is provided over the sidewall and a process, and a lithographic process is employed to form the circuit pattern on the sidewall 12. Alternatively, the conductive material can be applied by applying a conductive paste to the sidewall to form a circuit pattern of the balance reader, or alternatively, can be formed by applying a conductive ink to the sidewall to form thereon a circuit pattern of the balance reader. Polymeric paste can also be employed to form the circuit pattern and hardened by UV light to form the actual circuit. Surface mount soldering can be employed at regular oven temperatures and leather will withstand these temperatures.

In this embodiment, the card sleeve 28 can slidably receive a purse card 22 into a partition that is adjacent to the sidewall 22. As described above, the contact port can couple the partition holding the purse card with the partition that includes the electronic balance reader, such that among sliding purse card 22 into the first partition. The leads of the purse card 22 couple to the terminal points of the balance reader. A display element can be disposed on the sidewall 12 to provide to the user a display of the balance of purse card 22. In one embodiment, the display is positioned above the card sleeve 28 such that the display is disposed of location which would not be obstructed by placing the purse card 22 over the circuitry of the balance reader 36.

It will be understood to those of ordinary skill in the art of electrical engineering, the above invention can be modified or supplemented in order to provide alternative embodiments of a wallet that includes, integrated therein, a

balance reader suitable for reading an electronic purse card. However, such modifications are not deemed to depart from the scope of the invention, and are considered in the skill of an ordinary electrical engineer. Accordingly, the invention is not to be limited by the above description of the illustrated  
5   embodiments, but is to be defined by the claims as follows.

CLAIMS

What is claimed is:



- 1 1. Apparatus for reading the balance of an electronic money card,  
2 comprising  
3 a wallet having a first sidewall, and  
4 a card sleeve coupled to said sidewall and having a first partition that  
5 houses a balance reader having a contact for electrically communicating with a  
6 terminal point of said electronic money card, a second partition disposed  
7 adjacent to said first partition and dimensioned for slidably receiving an  
8 electronic money card, and a contact port for coupling said first partition to  
9 said second partition and disposed between said partitions to allow said contact  
10 to electrically couple with said terminal point.
- 1 2. Apparatus according to claim 1, wherein said card sleeve is formed of a  
2 non-conductive material.
- 1 3. Apparatus according to claim 1 wherein said balance reader includes a  
2 printed circuit board assembly.
- 1 4. Apparatus according to claim 1, wherein said balance reader includes a  
2 flex circuit board assembly.
- 1 5. Apparatus according to claim 1, wherein said balance reader includes an  
2 electronic assembly formed on said first sidewall of said wallet.
- 1 6. Apparatus according to claim 5, wherein said first sidewall includes  
2 leather.

- 1    7.     Apparatus according to claim 5, wherein said first sidewall includes  
2    canvas.
- 1    8.     Apparatus according to claim 5, wherein said first sidewall includes  
2    plastic.
- 1    9.     Apparatus according to claim 7, wherein said balance reader further  
2    includes a telecommunication element for exchanging data signals across a  
3    telephone communication line.
- 1    10.    Apparatus according to claim 9, wherein said telecommunication  
2    system includes an acoustic coupler.
- 1    11.    Apparatus according to claim 9 wherein said telecommunication system  
2    includes an electronic connection element for connecting to a telephone  
3    communication system.
- 1    12.    Processes for manufacturing a balance reader for an electronic money  
2    card, comprising the steps of  
3        providing a wallet having a first sidewall, and  
4        applying to said sidewall a conductive material to form a circuit pattern  
5    for said balance reader.
- 1    13.    Processes according to claim 12, including the further step of  
2        mounting circuit elements to said sidewall to form a circuit assembly  
3    thereon.
- 1    14.    Processes according to claim 12, wherein said step of applying  
2    conductive material includes the step of providing a mask over said sidewall.

1 15. Processes according to claim 12, wherein said step of applying  
2 conductive material includes the step of applying conductive paste to said  
3 sidewall.



1 16. Processes according to claim 12, wherein said step of applying  
2 conductive material includes the step of applying conductive ink to said  
3 sidewall.

1/2

**FIG. 1****FIG. 2**



2/2

**FIG. 3****FIG. 4**

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US97/15584

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G06K 5/00, 7/01, 19/00; G06F 17/00, 17/60

US CL : 235/ 380, 375, 382, 382.5, 279, 486, 487

According to International Patent Classification (IPC) r to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 235/ 380, 375, 382, 382.5, 279, 486, 487

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
NONE

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,221,838 A (Gutman et al.) 22 June 1993 (22/06/93), the entire reference	1-16
Y	US 5,514,862 A (Salzano) 07 May 1996 (07/05/96), the entire reference	1-16

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	* T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* A* document defining the general state of the art which is not considered to be of particular relevance	* X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* E* earlier document published on or after the international filing date	* Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* A* document member of the same patent family
* O* document referring to an oral disclosure, use, exhibition or other means	
* P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

19 DECEMBER 1997

Date of mailing of the international search report

13 JAN 1998

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

THIEN LE  
Telephone No. (703) 305-3500